

## RS32PVM

32" TFT Public Viewing Monitor with WDR Camera



### Key Features

- . 32" High Brightness Wide View Angle TFT LCD Display
- . Sleek Design & Single power source
- . Built in Wide Dynamic Range Colour Vari-Focal Camera
- . Integrated Surveillance & Advertisement Purpose
- . Built in SD card, support 4G capacity
- . IR Remote Controller
- . PIP & Multi-Language OSD



32" TFT Public Viewing Monitor with WDR Camera

MODEL	RS32PVM	
LCD Spec.	LCD Display	31.5" TFT Active Matrix panel
	Max. Resolution	1366(H) x 768(V)mm (WXGA)
	Lamp life time	60,000hrs
	Pixel Pitch	0.51075(H) x 0.51075(V)mm
	Contrast ratio(Typ.)	1500:1
	Brightness	500 nits
	Response time	8ms
	Viewing Angle	178°(H) / 178°(V)
Video 1 (WDR Camera) Spec.	Chip Brand	Sony
	Effective Pixels	NTSC: 768(H) x 494(V) PAL: 752(H) x 582(V)
	Resolution	>480TVL
	Min. Illuminatin	0.Lux (colour mode), 0.001Lux (DSS mode), 0.0003Lux (B/W mode)
	S/N Ratio (AGC off)	>48dB
	Wide Dynamic Range	ON/OFF Selectable on OSD menu
	Day & Night	ICR (auto/day/night), digital slow shutter
	Gain Control	OFF/low/mid/high selectable on OSD menu
	White Balance	Auto/hold/user selectable on OSD menu
	Flickerless	On/off selectable on OSD menu
Media Display	Lens Type	4~9mm/F1.6 auto iris vari-focal lens
	Audio speaker	Max power: 2W (Max.)
	IR Remote Control	YES
	Media display	SD/CF card loader
Others	Video display format	Support JPEG, MJPEG/III/IV, MP3
	Power	AC110~240V, 50/60Hz
	Power Consumption	180W
	Weight	26KG
	Dimensions (mm)	800(W) x 580(H) x 89(D)

specification subject to change without notice